



# PG

Pressure Gauges  
2", 2 1/2" & 4"  
1/8" & 1/4" Connection

### Function:

The BEECO Model Pressure Gauges are used for all suitable air and liquid systems for medium which does not clog connection ports or corrode copper alloy. Can be used in all water applications and can be used in both pneumatic systems and compressed air systems.

### Ratings:

Operating Temperatures Ambient -40°F to 140°F (-40°C to 60°C).  
Class: F+ 3/2/3% (ASMA B40.100 Grade B), KI 2.5 FOR 1/1/2" & 2", KI 1.6 for 3" & 4"  
Vacuum compound 0 to 60psi Accuracy

### Materials:

Case: Black Painted Steel, Window Acrylic (glass, acrltic glass, polycarbonate), NPT Connections: Brass, Movement: Semi-Brass, Pointer: Aluminum, Dial: Aluminum, Bourdon Tube: Copper Alloy.

### Features:

Gauges come in ranges from 0-30 psi up to 0-300 psi. In Top, Bottom and Back mounting options  
In both 1/8" NPT and 1/4" NPT connections.

## PGA.AA-B-BB-CC-XX

Face Size: 2" = 2.00  
2 1/2" = 2.50  
4" = 4.00

Pressure Reading Range (psi) ———  
BTM = Bottom Entry ———  
BK = Back Entry  
T = Top Entry

Connections: 1/8"NPT = .125  
1/4"NPT = .25



PG2.00-0-160-BTM-.25

Job Name: \_\_\_\_\_

Page No: \_\_\_\_\_

Section No: \_\_\_\_\_

Contractor: \_\_\_\_\_

Schedule No: \_\_\_\_\_

Purchase Order No: \_\_\_\_\_

Please consult BEECO engineering to get the latest updates On materials and specifications.

www.beecobackflow.com 1321 West 119th Street, Chicago IL, 60643  
BEECO Canada 150 Norfich Drive Unit 4, Toronto, Ontario, Canada  
M3N 1X6. Tel (416) 679-0380 Toll Free 1-800-387-3880