MIFAB, Inc.
1321 West 119th Street
Chicago, IL 60643-5109
Toll Free (800) 465-2736
Phone (773) 341-3030
Fax (773) 341-3049
E-Mail mail@mifab.com
Web Site www.mifab.com

July 2003

MIFAB Canada
150 Norfinch Drive Unit 4
Toronto, Ontario M3N 1X6
Toll Free (800) 387-3880
Phone (416) 679-0380
Fax (416) 679-0350

MIFAB – Fixture Carrier Systems

Features	Benefits
Most compact full featured carrier available.	Legs and face plate always factory assembled to save assembly labour. Legs are 18 inches high for ADA closet rough-in. Legs are invertible – no rights or lefts – same for both. Legs have 2 slots for anchor bolts in case of obstacle in floor (ie rebar) – only one bolt required.
Trim and fitting boxed separately.	Ease of handling and storage.
Bolts for closet height adjustment are located on front faceplate.	Easy access to allow for adjustment on water closet/fitting height. Labour savings on using an air gun with a battery of carriers. Stud obstruction eliminated with bolts on front of faceplate saving labour and time.
Two ½ inch tappings on back of faceplate.	Allows strut to be bolted flush to back of faceplate and notches in legs. Use of cushion clamp in strut allows for 4-3/4 inch rough-in from centre of cushion clamp to centre of nipple, allows for flush valve water supply rough-in. Anchor strut provides support for any additional rough-in. **Strut has multifunctional use.** Hodrite bracket fastens over hardware rods that support the water closets - can be used for 4-3/4 inch flush valve water supply rough-in.
Breakaway tabs on faceplate.	For fitting height adjustment. Very common dimensions to centre of water closet bowl when breaking off each tab. Rough-in height adjustment: Bottom of face plate to centre = 7 inch centre 1st cut = 6-1/4 inch centre 2nd cut = 5-1/2 inch centre 3rd cut = 5 inch center
Faceplate has additional 5/8 inch tapping.	The same faceplate to be inverted for blowout water closets installation.
Faceplate with O-rings.	Can receive any of 3 different nipple designs: -rolling threaded nipple - tapered nipple with running threaded horn adjustment - standard tapered threaded nipple

Features	Benefits
Feet are 3-1/2 inches deep.	Allows carrier legs to fit in 3-5/8 inch stud channel.
36 inch long barrel – MC-10-36-27	Only additional $50.00 List saves labour. Savings on cost of pipe and cutting pipe and no hub bands versus the competition. Always supplied with 2 inch waste connection auxiliary inlet to receive lavatory and/or urinal waste. Eliminates the need for a “Y” and/or “T” fitting if a lavatory and/or urinal are required.
¾ inch wider bolt slots for long barrel fitting.	Provides necessary adjustment to achieve required slope.
Threaded rods protective casing.	Protects threads during installation.
Closet support rods have double tightening nut.	One for siphon jet – 4 studs Second for blowout toilet – 3 studs (by turning faceplate upside down). Ensures steadfast connection.
1 inch leg notches from ground	Grip a 1-1/2 inch angle iron to transport a battery of carriers to the job site.
½ inch increments on legs/faceplate.	Visual reference for toilet height adjustment.
All tapped holes are greased.	For ease of installation for threaded rods.