


F1100

FLOOR DRAIN FOR NON-MEMBRANE FLOOR AREAS

Specification: MIFAB® Series F1100 (*)-1 (* specify strainer diameter) lacquered cast iron floor drain with anchor flange, and standard satin finished nickel bronze strainer with vandal resistant stainless steel allen key screws. (For membrane floors, add -C to the Series number).

Function: Used in showers, kitchens, restrooms, and other non-membrane finished areas. Round adjustable nickel bronze strainer is used for all types of poured finished floors.









(*) Denotes Strainer Size (**) Denotes Strainer Finish (-1, -3 or -4)



STRAINER DIAMETER	STRAINER ADJUSTMENT		ANSI/ASME RATING				BODY HEIGHT				
	MIN	MAX	FREE AREA	LOAD RATING		PIPE SIZE	NO HUB	PUSH	THREADED	INSIDE	PVC/ABS
				N.B. (-1)	S.S. (-3)	OIZL	(STANDARD)	ON (P)	(T)	CAULK (X)	(-30)/(-31)
5" (127)	1/2" (38)	1 1/2" (38)	8 in ² (52002)	Up To 2000 Lbs.	5000 lbs to 7499 lbs	2" (51)	3" (76)	3 3/8" (86)	2 1/4" (57)	3 3/4" (95)	2 15/16" (75)
6" (152)	11/16" (17)	1 1/2" (38)	9 in² (58002)	Up To 2000 Lbs.		3" (76)	3" (76)	3 3/8" (86)	2 5/8" (67)	3 3/4" (95)	3 3/4" (95)
7" (178)	9/16" (14)	1 9/16" (40)	12 in² (77002)	Up To 2000 Lbs.		4" (102)	3" (76)	3 3/8" (86)	2 5/8" (67)	3 3/4" (95)	3 3/4" (95)
8" (203)	1 1/16" (17)	2 1/4" (57)	18 in² (116002)	Up To 2000 Lbs.		5" (127)	3" (76)	-	2 5/8" (67)	3 3/4" (95)	-
10" (254)	1 1/16" (17)	2 1/4" (57)	26 in ² (171702)	Up To 2000 Lbs.		6" (152)	3 1/4" (83)	6 1/2" (165)	_		-

SUFFIX	OPTIONAL VARIATIONS
-1	Nickel bronze strainer (standard)
-3	Stainless steel strainer
-4	Ductile iron strainer (5", 8" only)
-5	Sediment bucket
-6	Security screws (T-20 Torx & pin)
-7	1/2" trap seal primer connection
-8	Backwater valve (2", 3", 4")
-11	Acid resistant epoxy coated body
-13	Galvanized body
-15	Extension
-21	Secondary flat stainless steel strainer (2", 3", 4")
-29	Stainless steel body (Type 316)
-30	PVC socket connection body
-31	ABS socket connection body
-34	Closure plug
-40	Underdeck clamp
-41	Sump receiver

-49	Chrome plated strainer			
-69	Stainless Steel sediment bucket			
-90	Threaded side outlet (2", 3", 4") (cast iron only)			
-90NH	No hub side outlet (2", 3", 4") (cast iron only)			
-95	Client logo			
-ARRA	American Iron and Steel Act Compliant			
-ВА	Minimum 51% material cost made in the USA			
-C	Membrane clamp for low rough-in (min. 1/2" (13))			
-C2	High rough-in membrane clamp (min. 1 9/16" (40)			
-F4	4" Round funnel			
-F6	6" Round funnel			
-G	Oval 4" x 9" funnel			
-HP	Heel proof grate (1/4" maximum grate opening size, -3 only)			
-J	6" x 3" x 1" funnel			
-MG	MI-GARD Floor Drain Trap Sealer (2", 3" or 4")			
P	Push on outlet			
-PA	Pennsylvania Steel Act compliant product			
Т	Threaded outlet (2", 3", 4")			
X	Inside caulk outlet			
-Z	Extended wide elastomeric flange			

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name:	Page No:
Section No:	Contractor:
Schedule No:	Purchase Order No: