

Location: _____



MC-14

VERTICAL, FIXED, ON-STACK WATER CLOSET CARRIER

Specification: MIFAB® Series MC-14 single, vertical, fixed, water closet carrier with lacquered cast iron fitting, 3" (76) or 4" (102) no hub waste (specify), 2" (51) or 4" (102) no hub vent connection (specify), lacquered cast iron faceplate, universal floor mounted cast iron foot supports, adjustable 8" tapered thread ABS nipple with integral test cap, neoprene bowl gasket, hardware, threaded rod protectors, polished chrome plated finishing cap nuts and rear anchor tie down support.

Function: Used with single water closets installed with the waste line below the floor slab. Common in hospitals, extended living and other facilities that have one water closet in each room. Can also be used within a horizontal battery of MC-10 fixture carriers if pipe space is limited and the horizontal wasteline can be installed below the floor slab. Typical for off the floor plumbing fixtures that are wall mounted and have no contact with the finished floor. The closet carrier is completely concealed within the wall and supports the load of the fixture through a faceplate and foot support system that is anchored to the floor. Sanitation underneath the fixture is more efficiently and economically maintained when installed off of the floor compared to floor mounted.

Note: 8 1/2" (216) minimum space required between front of foot and rear of anchor support with 4" (102) waste fittings and 7 3/8" (187) required with 3" waste fittings.

Note: Foot supports and faceplate are assembled at the factory before shipment in the typical siphon jet water closet configuration and are reversible for the blowout water closet design.

FRONT VIEW

FOOT SUPPORTS SHOULD BE SECURELY ANCHORED TO FLOOR WITH 1/2" (13) BOLTS AND ANCHORS BY OTHERS. ONLY 1 BOLT IS REQUIRED PER FOOT.

INLET C/L TO FLOOR ADJ. RANGE	
MIN	MAX
4 1/2"	9 1/2"

INLET C/L TO TOP FITTING	
MODEL	DIMENSION
MC-14-3-V2	3 3/4" [95]
MC-14-4-V2	6 1/2" [166]
MC-14-4-V4	4 1/2" [114]

Note: Rear anchor support is included with every Left and Right carrier.
Note: MC-14 Series Meets ANSI/ASME fixture carrier standard A112.6.1M-97 500 Lb. Load Rating with Rear anchor support.

TOP VIEW

Note: 8" tapered thread ABS nipple shipped standard with MC-14 Series carriers. The universal faceplate assembly accepts all nipple variations, rolling thread (-OR), cast iron (-CI) and tapered thread ABS with adjustable horn (-AH).

— "X"=4" MIN TO 6-1/4" MAX WALL THICKNESS WITH STANDARD NIPPLE. MIN OF 5/8" POSSIBLE WITH SHORTENED NIPPLE.

MODEL NUMBER	A	B	C
MC-14-3-V2	4 3/4" [89]	3 1/4" [83]	6 1/2" [165]
MC-14-4-V2	4 7/8" [100]	3 3/8" [86]	7 1/8" [181]
MC-14-4-V4	4 7/8" [100]	3 3/8" [86]	7 1/8" [181]

MC-14 Series Meets ANSI/ASME fixture carrier standard A112.6.1M-97 500Lb. Load Rating

SUFFIX	OPTIONAL VARIATIONS
-AH8	8" ABS nipple with adjustable horn
-AH12	12" ABS nipple with adjustable horn
-ASY	Prefabricated carriers
-BA	Buy American Act compliant product
-CI-4	4" rolling thread cast iron nipple
-CI-6	6" rolling thread cast iron nipple
-CI-8	8" rolling thread cast iron nipple
-CI-12	12" rolling thread cast iron nipple
-CI-24	24" rolling thread cast iron nipple
-FM	Floor mount, back outlet fixture support
-HD-750	750 lb. rated heavy duty
-HDX	1,000 lb. rated extra heavy duty
-HS	Hub and spigot connection
-OR8	8" rolling thread ABS nipple

-OR12	12" rolling thread ABS nipple
-PA	Pennsylvania Steel Act compliant product
-O1	Neoprene bowl gasket
-1	Finishing / Tiling frame
-3	Rear anchor support (Standard)
-10	Auxiliary support, recommended with nipple lengths over 12"
-12	12" tapered thread ABS nipple
-13	All galvanized
-14	Vandal proof finish trim
-17	Test plug for custom cast iron nipples
-19	Nipple wrench
-20	Flush valve support
-25	2" Auxiliary inlet, right side
-26	2" Auxiliary inlet, left side
-31	Two 2" Auxiliary inlets

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name: _____	Page No: _____
Section No: _____	Contractor: _____
Schedule No: _____	Purchase Order No: _____