


MI-GARD®

FLOOR DRAIN TRAP SEAL

Specification: MIFAB® MI-GARD® Series inline floor drain trap seal with UV resistant ABS plastic frame, silicon rubber sealing flapper and four flexible sealing ribs. Tested and certified to the ASSE 1072 Standard and listed with IAPMO and I.P.C. Specify connection size (1 1/2", 2", 3", 3 1/2", 4" or 6"). 10 year warranty is included.

Function: Used in the outlet connections of floor drain bodies, or the inside of floor drain strainers to seal the opening to prevent odors, sewer gases, and insects from entering up through the floor drain grate. The MI-GARD®'s four flexible silicone sealing ribs ensure easy installation into openings that have variations in size. The MI-GARD® will open to allow drainage and close when there is no water flow. MI-GARD can be used independent or in conjunction with trap seal primers for added protection against sewer gases and insects entering up through the floor drain grate. MI-GARD is not designed to substitute the trap seal primers.





SILICON GASKET FLEXES .100" TO FIT DIAMETER





MI-GARD-1.5




BOTTOM OF BODY



TOP OF STRAINER

1	Note: The MI-GARD-6 is designed in accordance with industry
	standards but is not IAPMO listed. All MI-GARD Floor Drain
	Trap Seals are in compliance with International Plumbing Code
	(LDC)









MI-GARD-3,4 and 6 are I.C.C. and BMEC approved.



MI-GARD® prevents the following from entering through the top of floor drains:

-Odors -Sewer gases -Insects

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name:	Page No:
Section No:	Contractor:
Schedule No:	Purchase Order No: