

R1220-R

MEDIUM SUMP ROOF DRAIN WITH INTEGRAL 2" WATER DAM

LACQUERED CAST IRON BODY WITH:

| MODEL NUMBER | WT.Lbs | OUTLET SIZE (NO HUB STANDARD) | CAST IRON DOME(-M) |
|---------------|--------|-------------------------------|--------------------|
| R1222,3,4,6-R | 21.00 | 2",3",4",6" | \$820.00 |

R1220-R OPTIONAL VARIATIONS

| SUFFIX | DESCRIPTION | LIST PRICE |
|--------|---|------------|
| -6 | Vandal proof (Metal dome only)(H-1029) | \$116.00 |
| -11 | Acid resistant epoxy coated body, membrane clamp & dome | \$1,016.00 |
| -12 | Galvanized metal dome | \$127.00 |
| -12A | Galvanized body and membrane clamp | \$329.00 |
| -13 | Galvanized body, membrane clamp and dome | \$393.00 |
| -83 | Stainless steel mesh screen over dome | \$465.00 |
| -B | Sump receiver (A5-BP) | \$256.00 |
| -C | Secondary clamp (A5-C3) | \$150.00 |
| -E | Adjustable extension (See page 114, point #7) | \$503.00 |
| -EG | Galvanized adjustable extension | \$1,126.00 |
| -G | Ballast guard (A5-BG) | \$626.00 |
| -HC | Adj. ballast guard with secondary clamp | \$776.00 |

| | | |
|------|---|------------|
| -JC | Ballast guard with secondary clamp | \$776.00 |
| -R | 2" external water dam (A5-WD) | \$194.00 |
| -U | Underdeck clamp (A5-C3) | \$150.00 |
| -U3 | Underdeck clamp with cut away side (A5-C3-U) | \$150.00 |
| -W-1 | Water proofing flange (A5-W-1) | \$440.00 |
| X | Inside caulk outlet, (2", 3", 4", 5" or 6") | No Add |
| -Z | Extended wide flange on body (20" Dia. x 1/4 thick) | \$1,313.00 |
| -5 | Cast iron sediment bucket (A2-MB) for R1220-PR only | \$256.00 |