T1500 Gratings — T1500 - 4” Internal body width

Gratings FILCOTEN HPC T1500 with fiX self-locking system

Model Number	Grate Type	Material	Dimensions	Load Class per EN 1433 / ANSI A112.21.1M	Slot / Mesh Width	Weight		Inlet cross-section (Free Area)	List Price, Each, Add	List Price, Per Foot, Add
						LBS	Kg.			
T1500-PG-FSA	Slotted	galvanized steel	39.40"/4.80"/.78"	A - Light Duty	0.31" wide x 3.15" slots (8x80mm)	8.0	3.64	42.63 sq. inches	$37.50	$11.43
T1500-PG-FSA-500	Slotted	galvanized steel	19.70"/4.80"/.78"	A - Light Duty	0.31" wide x 3.15" slots (8x80mm)	4.0	1.82	21.31 sq. inches	$30.00	$18.29
T1500-PG-FSSA	Slotted	stainless steel	39.40"/4.80"/.78"	A - Light Duty	0.31" wide x 3.15" slots (8x80mm)	8.0	3.64	42.63 sq. inches	$225.00	$68.60
T1500-PG-FSSA-500	Slotted	stainless steel	19.70"/4.80"/.78"	A - Light Duty	0.31" wide x 3.15" slots (8x80mm)	4.0	1.82	21.31 sq. inches	$180.00	$109.76
T1500-PG-WW	Wedgewire (non slip)	stainless steel	39.40"/4.80"/.78"	B - Medium Duty	0.24" wide x 1.61" slots (6 x 41 mm)	8.0	3.64	93.80 sq. inches	$815.00	$248.48
T1500-PG-WW-500	Wedgewire (non slip)	stainless steel	19.70"/4.80"/.78"	B - Medium Duty	0.24” wide x 1.61” slots (6x41 mm)	4.0	1.82	46.1 sq. inches	$425.00	$259.15
T1500-PG-FSC	Slotted	galvanized steel	39.40"/4.80"/.78"	C - Heavy Duty	0.31” wide x 3.15” slots (8x80 mm)	9.92	4.5	42.63 sq. inches	$193.75	$59.07
T1500-PG-FSC-500	Slotted	galvanized steel	19.70"/4.80"/.78"	C - Heavy Duty	0.31” wide x 3.15” slots (8x80 mm)	4.85	2.2	21.31 sq. inches	$157.50	$96.04
T1500-PG-FSSC	Slotted	stainless steel	39.40"/4.80"/.78"	C - Heavy Duty	0.31” wide x 3.15” slots (8x80 mm)	9.92	4.5	42.63 sq. inches	$517.50	$157.77
T1500-PG-FSSC-500	Slotted	stainless steel	19.70"/4.80"/.78"	C - Heavy Duty	0.31” wide x 3.15” slots (8x80 mm)	4.85	2.2	21.31 sq. inches	$412.50	$251.52
T1500-PG-FPC	Perforated (Heel Safe)	galvanized steel	39.40"/4.80"/.78"	C - Heavy Duty	Ø 1/4” hole (6.0 mm)	7.27	3.3	20.77 sq. inches	$225.00	$68.60
T1500-PG-FPC-500	Perforated (Heel Safe)	galvanized steel	19.70"/4.80"/.78"	C - Heavy Duty	Ø 1/4” hole (6.0 mm)	3.74	1.7	10.39 sq. inches	$180.00	$109.76
T1500-PG-FSPC	Perforated (Heel Safe)	stainless steel	39.40"/4.80"/.78"	C - Heavy Duty	Ø 1/4” hole (6.0 mm)	7.27	3.3	20.77 sq. inches	$701.25	$213.80
T1500-PG-FSPC-500	Perforated (Heel Safe)	stainless steel	19.70"/4.80"/.78"	C - Heavy Duty	Ø 1/4” hole (6.0 mm)	3.74	1.7	10.39 sq. inches	$431.25	$262.96
T1500-PG-PGC	Honeycomb (Heel Safe)	plastic	19.40"/4.84"/.78"	C - Heavy Duty	Ø 0.28" hole (7.2 mm)	2.42	1.1	22.47 sq. inches	$109.00	$66.46
T1500-PG-FMC	Mesh	galvanized steel	39.40"/4.80"/.78"	C - Heavy Duty	MW 1.18" x 0.39" (MW 30 mm x 10 mm)	7.28	3.3	141.05 sq. inches	$202.50	$61.74
T1500-PG-FMC-500	Mesh	galvanized steel	19.70"/4.80"/.78"	C - Heavy Duty	MW 1.18" x 0.39" (MW 30 mm x 10 mm)	3.53	1.6	68.59 sq. inches	$161.25	$98.32
T1500-PG-FMSC	Mesh	stainless steel	39.40"/4.80"/.78"	C - Heavy Duty	MW 1.18" x 0.39" (MW 30 mm x 10 mm)	7.28	3.3	141.05 sq. inches	$660.00	$201.22
T1500-PG-FMSC-500	Mesh	stainless steel	19.70"/4.80"/.78"	C - Heavy Duty	MW 1.18" x 0.39" (MW 30 mm x 10 mm)	3.53	1.6	68.59 sq. inches	$528.75	$322.41
T1500-PG-SL	Paverslot (Heel Safe)	galvanized steel	39.40"/4.84"/5.24"	C - Heavy Duty	SW 2x0.24" (2 x 65 mm)	12.8	5.8	18.6 sq. inches	$360.00	$109.76
T1500-PG-SL-500	Paverslot (Heel Safe)	galvanized steel	19.70"/4.84"/5.24"	C - Heavy Duty	SW 2x0.24" (2 x 65 mm)	6.61	3	9.3 sq. inches	$218.00	$132.93
T1500-SL-M	Maintenance Unit for Paverslot (Heel Safe)	galvanized steel	19.70"/4.84"/5.24"	C - Heavy Duty	SW 2x0.24" (2 x 65 mm)	11.7	5.3	9.3 sq. inches	$544.00	$165.85
T1500-PG-SSL	Paverslot (Heel Safe)	stainless steel	39.40"/4.84"/5.24"	C - Heavy Duty	SW 2x0.24" (2 x 65 mm)	12.8	5.8	18.6 sq. inches	$593.00	$180.79
T1500-PG-SSL-500	Paverslot (Heel Safe)	stainless steel	19.70"/4.84"/5.24"	C - Heavy Duty	SW 2x0.24" (2 x 65 mm)	6.61	3	9.3 sq. inches	$357.00	$217.68
T1500-SSL-M	Maintenance Unit for Paverslot (Heel Safe)	stainless steel	19.70"/4.84"/5.24"	C - Heavy Duty	SW 2x0.24" (2 x 65 mm)	11.7	5.3	9.3 sq. inches	$882.00	$268.90
T1500-PG-4-ADA	Longitudinal bar (Heel Safe)	ductile iron	19.70"/4.80"/.78"	C - Heavy Duty	1.14" x .24" (29 mm x 6.0 mm)	7.93	3.6	24.80 sq. nches	$86.25	$52.59
T1500-PG-4-13-ADA	Longitudinal bar (Heel Safe)	galvanized ductile iron	19.70"/4.80"/.78"	C - Heavy Duty	1.14" x .24" (29 mm x 6.0 mm)	7.93	3.6	24.80 sq. inches	$175.00	$106.70
T1500-PG-4-KIA	KIA (Heel Safe)	ductile iron with KIA pattern	19.70"/4.80"/.78"	D - Extra Heavy Duty	SW 3.94" x 0.22" (SW 100 x 5.7 mm)	9.48	4.3	32.95 sq. inches	$120.00	$73.17
T1500-PG-4-VIA	VIA (Heel Safe)	ductile iron with VIA	19.70"/4.80"/.78"	D - Extra Heavy Duty	SW 1.41" x 0.23" (SW 29 x 6 mm)	9.48	4.3	30.25 sq. inches	$120.00	$73.17
T1500-PG-4-WVY	WAVE (Heel Safe)	ductile iron with WAVE pattern	19.70"/4.80"/.78"	D - Extra Heavy Duty	SW 0.31" (SW 8 mm)	8.03	3.6	34.10 sq. inches	$120.00	$73.17
T1500-PG-4	Slotted	ductile iron	19.70"/4.80"/.78"	E - Extra Heavy Duty	0.55” wide x 3.94” slots (14x100 mm)	8.38	3.8	36.00 sq. inches	$105.00	$64.02
T1500-PG-4-13	Slotted	galvanized ductile iron	19.70"/4.80"/.78"	E - Extra Heavy Duty	0.55” wide x 3.94” slots (14x100 mm)	8.38	3.8	36.00 sq. inches	$225.00	$137.20
T1500-PG-4-VILLE	VILLE (Heel Safe)	ductile iron	19.70"/4.80"/.78"	E - Extra Heavy Duty	0.31” wide slots (SW 8 mm)	11.5	5.2	24.80 sq. inches	$165.00	$100.61

Note: The maximum flow rate represents the maximum flow in the trench itself.
The number and size of the outlets will determine the maximum flow rate of the trench system.