

TOOO

| Grate Part Number | Suffix | Description | Material | Weight (lbs./ft.) | Length | Width | Free Area (sq. in. per ft.) | Slot Width / Hole Size | ADA | Load Ratings | | | |
|----------------------|---------|--------------------------|---------------------|----------------------|-------------|------------|--------------------------------|--------------------------------------------------------------------------------------|---------|---------------------|--------------|------|-----|
| | | | | | | | | | | DIN | ANSI | H-20 | FAA |
| | Note: T | wo of the T20 | 00-PG-PVC gra | ates are ree | quired to a | attain a 2 | 4" x 24" grate o | limension as e | each gr | ate is ^r | 12" x 24" | | |
| [2000-PG-RGS | -RGS | Reinforced Slotted | Galvanized Steel | 46.20 | 24" | 24" | 101.00 | 0.380" | Yes | В | Light Duty | No | No |
| Г2000-PG-RFS | -RFS | Reinforced Slotted | Stainless Steel | 47.50 | 24" | 24" | 101.00 | 0.380" | Yes | В | Light Duty | No | No |
| T2000-PG-RG | -RG | Reinforced Perforated | Galvanized Steel | 46.70 | 24" | 24" | 62.52 | 0.250" Dia. | Yes | В | Light Duty | No | No |
| T2000-PG-RPS | -RPS | Reinforced Perforated | Stainless Steel | 48.00 | 24" | 24" | 62.52 | 0.250" Dia. | Yes | В | Light Duty | No | No |
| T2000-PGF-4 | -PGF-4 | Slotted Grate | Ductile Iron | 73.40 | 24" | 12" | 111.90 | 1.030" | No | F | Special Duty | Yes | Yes |
| | Note: 1 | Two of the T2 | 000-PGF-4 grat | es are req | uired to a | ttain a 24 | " x 24" grate di | mension as ea | ach gra | te is 1 | 2" x 24" | | |
| | | | | | | | | 12" x 12" Grate for T1350-FL, T1360-FL and T1360-FL-TH Trench Drain Systems | | | | | |

T2000-PG-RG / RPS



F1440-PG-4

Note: Two of the T2000-PGF-4 grates are required to attain a 24" x 24" grate dimension as each grate is 12" x 24"

T2000-PG-RGS / RFS

T2000-PGF-4

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Design and dimensions are subject to modification. Prices do not include applicable taxes. MIFAB®, Inc., 1321 West 119th Street, Chicago, Illinois 60643-5109, USA All sales subject to MIFAB's® Terms and Warranties. Please refer to inside back cover. Visit www.mifab.com for the most recent product information.

Toll Free: 1-800-465-2736, Fax: 1-773-341-3049 sales@mifab.com Canada Toll Free: 1-800-387-3880